



X3.060 F - X3.070 F - X3.080 F-GE

  
**McCormick**  
Power Technology.

		X3.060 F	X3.070 F	X3.080 F - GE
<b>MOTOR</b>				
Putere Maxima ISO	hp/kW	54.5 / 40	68 / 50	75 / 54.5
Putere nominala	rpm	2200		
Cuplu maxim	Nm	260	315	315
Producator		2.5 Kohler KDI		
Stage V / Tier 4 Final exhaust gas after-treatment		EGR/DOC		
Cilindri / Capacitate cilindrica / Valve	cm <sup>2</sup>	4 / 2.5 L / 16		
Capacitate rezervor	l	50		
<b>AMBREIAJ</b>				
Model		11" - independent dry dual clutch		
Control		● mecanic		
<b>TRANSMISIE</b>				
Numar trepte de viteza		● 12 FWD + 12 REV without creeper - ○ 16 FWD + 16 REV with creeper		
<b>FRONT AXLE</b>				
Tractie		Cuplare electrohidraulica a tractiunii integrale		
Unghi maxim de virare		55°		
Scara diferential spate		100% electro-hydraulic		
<b>SISTEME DE FRANARE</b>				
Sistem de franare fata		Cuplare automata a tractiunii integrale la franare		
Sistem de franare spate		Frane multidiscs umede		
Sistem de franare a remorcii		○ Franare hidraulica a remorcii sau franare hidraulica conform directivelor MR si CE		
<b>SISTEM HIDRAULIC</b>				
Pompa hidraulica a cuplajului spate - debit	l/min	50		
Pompa de directie - debit	l/min	30		
Cupape spate: tip, min - max		mechanical, 1 - 3		
<b>CUPLARE SPATE IN 3 PUNCTE</b>				
Cuplaj spate controlat mecanic		Controlul tractiunii cu cuplaj in 3 puncte: controlul pozitiei, control mixt, pozitie flotanta		
Capacitate standard de ridicare	kg	● 2200		
<b>PRIZA DE PUTERE SPATE</b>				
		mecanica		
Viteza	rpm	540 / 540+540E / 540+1000		
Rotatie - tip arbore cu caneluri		In sensul acelor de ceasornic ● 13/8" arbore cu 6 caneluri		
Ground speed PTO		●		
<b>SISTEM 3-PUNCTE FATA</b>				
Capacitate maxima de ridicare	kg	1000		
<b>PRIZA DE PUTERE FATA</b>				
Turatii	rpm	1000		
<b>CABINA</b>				
Volanta cu profil redus		○		
Aer conditionat		●		
Volant de control digital		●		
Lumini de lucru LED		○		
Volanta montata ISO		●		
<b>DIMENSIUNII SI GREUTATI - MODELS WITH ROPS (IN RUNNING ORDER)</b>				
Inaltimea 4WD	mm	3652		
Latime minima	mm	1358		
Wheelbase 4WD	mm	1950		
Inaltimea minima	mm	2214		
Latime minima la sol	mm	186		
Greutati	kg	2200		
<b>ECHIPARE OPTIONALA</b>				
Greutati frontale-24 kg fiecare		○		

All data and illustrations provided in this brochure are for information purposes only and can be changed.



G. Matteotti, 7 | 42042 Fabbrico [RE] Italia  
 +39.0522.656.111 | f. +39.0522.656.476  
 master@argotractors.com | www.argotractors.com

